



Coil and Filter Data

COIL FACE AREA AND FILTER DATA

Unit Size	Internal Cooling And Heating Coils	Discharge Section Heating Coil	2" Filters (Quantity) and Size	Filter Face Area
08	2.1 [0.20]	2.1 [0.20]	(1) 16 x 20 x 2 [406 x 508 x 51]	2.2 [0.20]
12	2.8 [0.26]	2.1 [0.20]	(1) 20 x 20 x 2 [508 x 508 x 51]	2.8 [0.26]
16	3.6 [0.33]	3.2 [0.30]	(1) 24 x 24 x 2 [610 x 610 x 51]	4.0 [0.37]
20	4.8 [0.45]	3.2 [0.30]	(1) 24 x 24 x 2 [610 x 610 x 51]	4.0 [0.37]
25	5.7 [0.53]	4.6 [0.43]	(1) 24 x 24 x 2 [610 x 610 x 51] (1) 12 x 24 x 2 [305 x 610 x 51]	6.0 [0.56]
30	6.8 [0.63]	5.7 [0.53]	(1) 24 x 24 x 2 [610 x 610 x 51] (1) 12 x 24 x 2 [305 x 610 x 51]	6.0 [0.56]

Notes:

- Standard filters are 2" throwaway; optional filters are 2" pleated
- Filter sizes are nominal and standard size, measured in inches [millimeters]
- Coil and filter face areas are measured in square feet [square meters]

NOMINAL COIL CONNECTION SIZES

Unit Size	Coil Type											
	Water				Steam				Refrigerant			
	1 Row	2 Row	4 Row	6 Row	1 Row		2 Row		4 Row		6 Row	
					STM.	COND.	STM.	COND.	Liquid	Suction	Liquid	Suction
08	5/8 [16]	5/8 [16]	7/8 [22]	7/8 [22]	1 1/8 [29]	7/8 [22]	1 1/8 [29]	7/8 [22]	5/8 [16]	5/8 [16]	5/8 [16]	5/8 [16]
12	5/8 [16]	5/8 [16]	7/8 [22]	7/8 [22]	1 1/8 [29]	7/8 [22]	1 1/8 [29]	7/8 [22]	5/8 [16]	7/8 [22]	5/8 [16]	7/8 [22]
16	5/8 [16]	5/8 [16]	7/8 [22]	1 1/8 [29]	1 1/8 [29]	7/8 [22]	1 3/8 [35]	1 1/8 [29]	5/8 [16]	7/8 [22]	5/8 [16]	7/8 [22]
20	5/8 [16]	5/8 [16]	7/8 [22]	1 1/8 [29]	1 3/8 [35]	1 1/8 [29]	1 3/8 [35]	1 1/8 [29]	5/8 [16]	7/8 [22]	5/8 [16]	7/8 [22]
25	5/8 [16]	7/8 [22]	1 1/8 [29]	1 3/8 [35]	1 3/8 [35]	1 1/8 [29]	1 5/8 [41]	1 1/8 [29]	5/8 [16]	7/8 [22]	5/8 [16]	1 1/8 [29]
30	7/8 [22]	7/8 [22]	1 1/8 [29]	1 3/8 [35]	1 5/8 [41]	1 1/8 [29]	1 5/8 [41]	1 1/8 [29]	5/8 [16]	1 1/8 [29]	5/8 [16]	1 1/8 [29]

Notes:

- Water coils are based on Standard GPM Circuiting. Consult factory for applications requiring special circuiting
- For other selections, refer to RAMP
- Refrigerant coil connection sizes for single circuit coils and may vary with application. Contact Superior Rex for double circuit coils
- All dimensional data is outside diameter (O.D.), measured in inches [millimeters]

Performance Data

COIL DATA

COILS

Superior Rex manufactures hot water, chilled water, direct expansion (DX), and standard steam coils for specific application with all Model SSL/SBS blower coils. AHRI 410 certified and labeled, and strict on-site

inspection before, during, and after installation guarantees the highest quality and performance available.

Standard Features

- » Designed, manufactured and tested by Superior Rex
- » AHRI 410 certified and labeled
- » ½" O.D. seamless copper tubes
- » High efficiency aluminum fin surface for optimizing heat transfer, pressure drop and carryover
- » Mechanically expanded copper tubes leak tested to a minimum 450 PSIG air pressure under water
- » Manual air vent plug on all water coils
- » Copper ODM sweat connections
- » 300 PSIG working pressure at 200°F
- » Evaporator coils are factory sealed and charged with a minimum of 5 PSIG nitrogen or refrigerated dry air
- » Steam coils rated at 15 PSIG maximum operating pressure at above 35°F
- » 0.016" tube wall thickness (0.025" on steam)

Optional Features

- » Stainless steel coil casings
- » Automatic air vents on water coils
- » Elevated working pressure ratings
- » Heat pump compatible cooling coils
- » Double circuit DX coils (intertwined with 50-50 split)
- » 0.025" tube wall thickness



COMPONENT STATIC PRESSURE LOSS – INCHES W.G.

Unit Size	Nominal CFM	Cabinet	Filter (2" T/A)	Coil						Inlet Damper Section	Electric Heat Section
				Internal				External			
				1 Row	2 Row	4 Row	6 Row	1 Row	2 Row		
08	800	0.09	0.25	0.05	0.10	0.31	0.46	0.05	0.10	0.04	0.05
12	1200	0.09	0.25	0.06	0.12	0.37	0.55	0.10	0.19	0.06	0.05
16	1600	0.10	0.25	0.06	0.12	0.38	0.58	0.08	0.15	0.09	0.05
20	2000	0.11	0.25	0.06	0.11	0.35	0.52	0.11	0.22	0.05	0.05
25	2500	0.12	0.25	0.06	0.12	0.38	0.57	0.09	0.17	0.06	0.05
30	3000	0.14	0.25	0.06	0.12	0.38	0.57	0.08	0.16	0.08	0.05

Notes:

1. All static pressures are at nominal CFM
2. Coil static pressure for standard coil, 10FPI at 80/67 EAT and 45° EWT with 10° rise
3. For 12FPI, refer to RAMP
4. Filter static pressure based on 50% loaded filter
5. If pleated filters are used in lieu of throwaway, the filter static pressure loss is 0.35